


## The field-proven, digital soft start solution

## The XLD Series Ratings

39 - 1250 Amps



**Optional Disconnect** Blank = None

B = Circuit Breaker
F = Fusible Disconnect (39 & 48A models only)

Voltage Blank = 208 - 480V 600 = 208 - 600V

**Enclosure** 

**Control Power** 

**E** = NEMA 12 **N4** = NEMA 4/4X

by MO	TORTR	ONICS
-------	-------	-------

Model Number	MAX AMPS	Horsepower			KW		
		208V	240V	480V	600V	230V	400V
XLD-39*	39	10	-	25	30	11	18.5
XLD-48	48	10	15	30	40	-	22
XLD-62	62	15	20	40	50	15	30
XLD-78	78	20	25	50	60	22	37
XLD-92	92	25	30	60	75	-	45
XLD-120	120	30	40	75	100	30	55
XLD-150	150	40	50	100	125	45	75
XLD-180	180	50	60	125	150	55	90
XLD-220	220	60	75	150	200	-	110
XLD-288	288	75	100	200	250	75	132
XLD-360	360	100	125	250	300	110	160
XLD-414	414	125	150	300	350	-	200
XLD-476	476	-	-	350	400	132	250
XLD-550	550	150	200	400	500	160	-
XLD-718	718	200	250	500	600	200	315
XLD-862	862	250	300	600	700	-	400
XLD-1006	1006	300	350	700	800		550
XLD-1150	1150	350	400	800	900		637
XLD-1200	1200	400	450	900	1000		665
XLD-1250	1250	450	500	1000	1125		700